

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

Product Name: Hydrogen sulphide/inert gas mixture	Trade Name: Hydrogen sulphide/inert gas mixture
Product Use: Not available.	
Chemical Name: Not applicable.	Synonym: Not applicable.
Chemical Formula: Not applicable.	Chemical Family: Not applicable.
Telephone: Emergencies: * 1-800-363-0042	Supplier /Manufacture: Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2
	Phone: 905-803-1600
	Fax: 905-803-1682

**Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.*

2. Composition and Information on Ingredients

INGREDIENTS	% (VOL)	CAS NUMBER	LD ₅₀ (Species & Routes)	LC ₅₀ (Rat, 4 hrs.)	TLV-TWA (ACGIH)
Hydrogen sulphide AND CONTAINS ONE OR MORE OF THE FOLLOWING GASES:	0.0001-0.99	7783-06-4	Not applic.	356 ppm	10 ppm
Argon	Balance	7440-37-1	Not applic.	Not available.	Simple asphyxiant.
Helium	Balance	7440-59-7	Not applic.	Not available.	Simple asphyxiant.
Krypton	Balance	7439-90-9	Not applic.	Not available.	Simple asphyxiant.
Neon	Balance	7440-01-1	Not applic.	Not available.	Simple asphyxiant.
Nitrogen	Balance	7727-37-9	Not applic.	Not available.	Simple asphyxiant.
Xenon	Balance	7440-63-3	Not applic.	Not available.	Simple asphyxiant.

3. Hazards Identification

Emergency Overview

CAUTION! High-pressure gas. Can cause rapid suffocation. May cause dizziness and drowsiness. Self-contained breathing apparatus may be required by rescue workers.

ROUTES OF EXPOSURE: Inhalation.

Product Name: Hydrogen sulphide/inert
gas mixture

MSDS# E-6777-G

Date: 10/15/2007

THRESHOLD LIMIT VALUE: TLV-TWA Data from 2007 Guide to Occupational Exposure Values (ACGIH). TLV-TWAs should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations.

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION: Asphyxiant. Moderate concentrations may cause headaches, drowsiness, dizziness, excitation, excess salivation, vomiting, and unconsciousness. This mixture contains traces of hydrogen sulphide which may cause some irritation of the respiratory tract and damage the central nervous system if inhaled in large quantities. Lack of oxygen can kill.

SKIN CONTACT: No evidence of adverse effects from available information.

SKIN ABSORPTION: No evidence of adverse effects from available information.

SWALLOWING: Unlikely route of exposure. This product is a gas at normal temperature and pressure.

EYE CONTACT: No evidence of adverse effects from available information.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:

No evidence of adverse effects from available information.

OTHER EFFECTS OF OVEREXPOSURE:

None known. This product is an asphyxiant. Lack of oxygen can cause death.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Repeated or prolonged exposure is not known to aggravate medical condition.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:

Not available - mixture not tested.

CARCINOGENICITY:

Not listed as carcinogen by OSHA, NTP or IARC.

4. First Aid Measures

INHALATION:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SKIN CONTACT:

Wash contaminated skin with soap and water.

SWALLOWING:

This product is a gas at normal temperature and pressure.

EYE CONTACT:

Flush with water.

NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition.

5. Fire Fighting Measures

FLAMMABLE : No. **IF YES, UNDER WHAT CONDITIONS?** Not applicable.

FLASH POINT (test method) Not applicable. **AUTOIGNITION TEMPERATURE** Not applicable.

Product Name: Hydrogen sulphide/inert
gas mixture

MSDS# E-6777-G

Date: 10/15/2007

**FLAMMABLE LIMITS
IN AIR, % by volume:**

LOWER: Not applicable.

UPPER: Not applicable.

EXTINGUISHING MEDIA:

This mixture cannot catch fire. Use media appropriate for surrounding fire.

SPECIAL FIRE FIGHTING PROCEDURES:

CAUTION! High-pressure gas. Asphyxiant. Effects are due to lack of oxygen. Evacuate all personnel from danger area. Immediately deluge cylinders with water from maximum distance until cool; then move them away from fire area if without risk. Self-contained breathing apparatus may be required by rescue workers

UNUSUAL FIRE AND EXPLOSION HAZARD:

Nonflammable material. This material cannot catch fire. Container may rupture due to heat of fire. No part of a container should be subjected to temperature higher than 52 C. Most containers are provided with a pressure relief device designed to vent contents when they are exposed to elevated temperature. Toxic fumes may be produced when heated.

HAZARDOUS COMBUSTION PRODUCTS:

Not applicable.

SENSITIVITY TO IMPACT:

Avoid impact against container.

SENSITIVITY TO STATIC DISCHARGE:

Not applicable.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CAUTION! High-pressure gas. Evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Shut off flow if you can do so without risk. Ventilate area or move cylinder to a well-ventilated area. Test for sufficient oxygen, especially in confined spaces, before allowing reentry.

WASTE DISPOSAL METHOD:

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE:

Store and use with adequate ventilation. Separate flammable cylinders from oxygen, chlorine, and other oxidizers by at least 6 m or use a barricade of non-combustible material. This barricade should be at least 1.5 m high and have a fire resistance rating of at least ½ hour. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Post "No Smoking or Open Flames" signs in storage and use areas. There must be no sources of ignition. All electrical equipment in storage areas must be explosion-proof. Storage areas must meet national electric codes for Class 1 hazardous areas. Store only where temperature will not exceed 52 C. Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

PRECAUTIONS TO BE TAKEN IN HANDLING:

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. For other precautions, see section 16.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe*

Product Name: Hydrogen sulphide/inert gas mixture

MSDS# E-6777-G

Date: 10/15/2007

Handling of Compressed Gases in Containers, available from the CGA. Refer to section 16 for the address and phone number along with a list of other available publications.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:

High pressure gas. Use piping and equipment adequately designed to withstand pressures to be encountered. **Gas can cause rapid suffocation due to oxygen deficiency.** Store and use with adequate ventilation. Close valve after each use; keep closed even when empty. **Prevent reverse flow.** Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. **When returning cylinder to supplier,** be sure valve is closed, then install valve outlet plug tightly. **Never work on pressurized system.** If there is a leak, close the cylinder valve. Vent the system down in a safe and environmentally sound manner in compliance with all federal, provincial, and local laws; then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST: Preferred.

MECHANICAL (general): Acceptable.

SPECIAL: None.

OTHER: Not applicable.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: Select in accordance with provincial regulations, local bylaws or guidelines. Selection should also be based on the current CSA standard Z94.4, "Selection, Care and Use of Respirators". Respirators should also be approved by NIOSH and MSHA.

SKIN PROTECTION: Wear work gloves when handling cylinders.

EYE PROTECTION: Wear safety glasses when handling cylinders.

Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

9. Physical and Chemical Properties

PHYSICAL STATE: Gas.	FREEZING POINT: Not available - mixture not tested.	pH: Not available - mixture not tested.
BOILING POINT: Not available - mixture not tested.	VAPOUR PRESSURE: Gas.	MOLECULAR WEIGHT: Not applicable.
SPECIFIC GRAVITY: LIQUID (Water = 1) Not applicable.	SOLUBILITY IN WATER, Not available - mixture not tested.	
SPECIFIC GRAVITY: VAPOUR (air = 1) Not available - mixture not tested.	EVAPORATION RATE (Butyl Acetate=1): Not available.	COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable.

Product Name: Hydrogen sulphide/inert gas mixture

MSDS# E-6777-G

Date: 10/15/2007

VAPOUR DENSITY: Not available - mixture not tested. | % VOLATILES BY VOLUME: Not available. | ODOUR THRESHOLD: Not available.

APPEARANCE & ODOUR: Colourless. Rotten eggs.

10. Stability and Reactivity

STABILITY: The product is stable.

CONDITIONS OF CHEMICAL INSTABILITY: Not available.

INCOMPATIBILITY (materials to avoid): Not available - mixture not tested.

HAZARDOUS DECOMPOSITION PRODUCTS: Not available - mixture not tested.

HAZARDOUS POLYMERIZATION: Not available.

CONDITIONS OF REACTIVITY: None currently known.

11. Toxicological Information

See section 3.

12. Ecological Information

No adverse ecological effects expected. This product does not contain any Class I or Class II ozone-depleting chemicals. The components of this mixture are not listed as marine pollutants by TDG Regulations.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

14. Transport Information

TDG/IMO SHIPPING NAME: Compressed gas, n.o.s.

HAZARD CLASS:	IDENTIFICATION #:	PRODUCT RQ:
C L A S S 2 . 2 : Non-flammable and non-poisonous gas.	UN1956	Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more

SHIPPING LABEL(s): Non-flammable, non-poisonous gas

PLACARD (when required): Non-flammable, non-poisonous gas

SPECIAL SHIPPING INFORMATION:

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of vehicle can present serious safety hazards.

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

DSL (Canada) This product is on the DSL list

WHMIS (Canada) CLASS A: Compressed gas.

International Regulations

EINECS Not available.

DSCL (EEC) R20- Harmful by inhalation.

International Lists No products were found.

16. Other Information

MIXTURES:

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

HAZARD RATING SYSTEM:

HMIS RATINGS:

HEALTH 0

FLAMMABILITY 0

PHYSICAL HAZARD 2

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED: CGA-330

PIN-INDEXED YOKE: Not available.

ULTRA-HIGH-INTEGRITY CONNECTION: Not available.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

- AV-1 Safe Handling and Storage of Compressed Gas
- P-1 Safe Handling of Compressed Gases in Containers
- P-14 Accident Prevention in Oxygen-Rich, Oxygen-Deficient Atmosphere
- SB-2 Oxygen-Deficient Atmospheres
- V-1 Compressed Gas Cylinder Valve Inlet and Outlet Connections
- V-7 Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures
- Handbook of Compressed Gases, Fourth Edition

For more indepth information for each component, refer to the pure product MSDS.

The information contained in this MSDS is generated from technical sources using the Chemmate Mixture

Product Name: Hydrogen sulphide/inert
gas mixture

MSDS# E-6777-G

Date: 10/15/2007

MSDS system and the pure-product MSDS for each component. These mixtures are not tested as a whole for chemical, physical, or health effects.

PREPARATION INFORMATION:

DATE: 10/15/2007
DEPARTMENT: Safety and Environmental Services
TELEPHONE: 905-803-1600

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety information, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

Praxair and the *Flowing Airstream* design are trademarks of
Praxair Canada Inc.

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc.
1 City Centre Drive
Suite 1200
Mississauga, ON L5B 1M2